



There are two structures for choice as follows:

Mono-Block Slider



Open Slider



Features:

- .Manual power on/off
- .Metric/Inch system interchange at any position
- .Zero setting at any position
- .With data output interface
- .With fine adjustment

No.	Range mm/in	Resolution mm/in	J K	
			mm	mm
111-300	200/8	0.01/.0005	60	10
111-300-1	200/8	0.01/.0005	75	10
111-301	250/10	0.01/.0005	60	10
111-301-1	250/10	0.01/.0005	75	10
111-301-2	250/10	0.01/.0005	90	10
111-302	300/12	0.01/.0005	60	10
111-302-1	300/12	0.01/.0005	75	10
111-302-2	300/12	0.01/.0005	90	10
111-303	400/16	0.01/.0005	90	20
111-303-1	400/16	0.01/.0005	125	20
111-303-2	400/16	0.01/.0005	150	20
111-304	500/20	0.01/.0005	100	20
111-304-1	500/20	0.01/.0005	150	20
111-304-2	500/20	0.01/.0005	200	20
111-305	600/24	0.01/.0005	100	20
111-305-1	600/24	0.01/.0005	150	20
111-305-2	600/24	0.01/.0005	200	20
111-306	750/30	0.01/.0005	125	20
111-306-1	750/30	0.01/.0005	150	20
111-306-2	750/30	0.01/.0005	200	20
111-306-3	750/30	0.01/.0005	250	20

No.	Range mm/in	Resolution mm/in	J K	
			mm	mm
111-307	1000/ 40	0.01/.0005	150	20
111-307-1	1000/ 40	0.01/.0005	200	20
111-307-2	1000/ 40	0.01/.0005	250	20
111-307-3	1000/ 40	0.01/.0005	300	20
111-308	1500/ 60	0.01/.0005	150	20
111-308-1	1500/ 60	0.01/.0005	200	20
111-308-2	1500/ 60	0.01/.0005	250	20
111-308-3	1500/ 60	0.01/.0005	300	20
111-309	2000/ 80	0.01/.0005	150	20
111-309-1	2000/ 80	0.01/.0005	200	20
111-309-2	2000/ 80	0.01/.0005	250	20
111-309-3	2000/ 80	0.01/.0005	300	20
111-310	2500/100	0.01/.0005	150	20
111-310-1	2500/100	0.01/.0005	200	20
111-310-2	2500/100	0.01/.0005	250	20
111-310-3	2500/100	0.01/.0005	300	20
111-311	3000/120	0.01/.0005	150	20
111-311-1	3000/120	0.01/.0005	200	20
111-311-2	3000/120	0.01/.0005	250	20
111-311-3	3000/120	0.01/.0005	300	20